

# **Alcoa Wheel Accessories**



#### Cleaner

Super Shine Aluminum Polish is polished agent for daily maintenance for Alcoa forged wheel and degraded polish surface. It is possible to remove slight scratch. Heavy Duty Aluminum Wash is high acid agent and it is for removing thin oxide surface, refractory stain.

- X After using Aluminum Wash, Aluminum Polish care is necessary.
- \* These are not used for Dura Bright and other coated wheel.

Part No.	item	Content	Unit
44016	Super Shine Aluminum Polish	473ml	12 bottles
15016	Heavy Beauty Aluminum Wash	473ml	12 bottles



## **Disk Mate**

Disk Mate should be mounted between Hub and wheel in order to protect defect, dust, rust. In addition, it is useful for wear of Hub/Wheel, noise from wheel contact area. \*It is available for Alcoa forged aluminum wheel only.

Part No.	Hub(mm)	BattHale(mm)	Item			Unit
013000	335	30	22.5 inch	10 H	ISO wheel	10 pcs
014000	225	30	19.5 inch	8 H	ISO wheel	10 pcs
023000	221	40	22.5 inch	8 H	JIS wheel	10 pcs
0240001	165	25	16/17.5/19.5 inch	6 H	JIS wheel	10 pcs



## Sleeve Nut/Insert

The sleeve nut is for Arconic original nut for bolt hole diameter 32mm wheel, that are available wheel 766413, 878513 886513, 896513.there is two types screw threads for Metric and BSF. Sleeve goes into 32mm bolt hole and it is possible to mount Alcoa wheel without replacement for steel wheel stud bolt.

lem			remark		
M22-1.5 Right screw Single		Metric screw thread for Benz			
M22-1.5	Right screw	Double	Metric screw thread for Benz		
		Single	BSF screw thread for Scania		
7/8"-11 BSF	Right screw	Double	BSF screw thread for Scania		
Insert with Alcoa logo mark			Attachment for sleeve nut		
	M22-1.5 7/8"-11 BSF 7/8"-11 BSF	M22-1.5 Right screw M22-1.5 Right screw 7/8"-11 BSF Right screw 7/8"-11 BSF Right screw	M22-1.5 Right screw Single  M22-1.5 Right screw Double  7/8"-11 BSF Right screw Single		

\*The insert is involved in above sleeve when you purchase. Purchasing insert only is available.

XAbove picture is different from ARMS nut.





## **Grease**

FreyLube is water isolated grease. Please apply this grease at O-ring and grommet air valve as a proper quantity. It is useful for prevention for sticking wheel on hub by anti-freezing agent.

\*Don't stick on hub and a contact surface to hub.

Part No.	Item	Content	Unit
FL2000	FleyLube	2kg	1 case



### **Air Valve**

When you place order the valve, please check part number of wheel or valve part number.

\*Arconic recommend to replace new valve once a year.

			Assessed to the Party of the Pa		1818			
ValvePartNo.		WheelPartNo.						
TR543CN	250003	251003	260003	353013	353023			
TR543C	663113	663123	663133	663713	663733	763323	763353	764713
TR544C	653013	653023	663013	663823	873353	883353		
TR544D	663103 883343	810520 883533	813540	813542	841542	873323	873343	883323
TR542	813540	813542						
TR543D	663203							
60MS27N	874503 894573	884553 895553	884563	884573	885553	886503	894533	894553
70MS7SE	763423 896523	871523 896533	874523	881523	886513	886523	886533	896513
70MS7SL	878513	882523DB	*1					
70MS7	768423	768423DB	871523D	B 874523	BDB 8815	23DB 882	2523DB *1	

\*1: 70MS7SL and 70MS7 both are adoptable for 882523DB.



Howmet Systems Japan Ltd. 8F CIRCLES Nihonbashibakurocho 1-5-12 Nihonbashibakurocho, Chuo-ku Tokyo, 103-0002 Japan Tel:+81-3-5642-8351 Fax:+81-3-5644-5771